## INVITATION TO BID

# **Ada City Schools** 324 W. 20th Street Ada, Oklahoma 74820

### Mr. Mike Anderson, Superintendent – 580-310-7200

The Board of Education invites your company to bid on the following school bus(es), equipped as per these specifications.

All sealed bids must be received, no later than 3:00 p.m., Friday, May 25, 2018 at the Ada City Schools Board of Education Office, 324 West 20th; Ada, OK 74820. Bids will be opened at 3:15 p.m. on Friday, May 25, 2018 at the Ada City Schools Board of Education Office, 324 West 20th; Ada, OK 74820.

The Board of Education reserves the right to reject any or all bids and to award the bid to the lowest and/or best bidder. Buses must meet and/or exceed the State & Federal Minimum Requirements for School Buses, in effect for date of manufacture.

To facilitate a comparison of all brands of school buses being bid, all bids must be submitted on this form, with exceptions to specifications listed on a separate page, if required.

### GENERAL DESCRIPTION:

2019 Model Year, Conventional (Type C) School Bus

71 Passenger Capacity – Diesel Powered

#### SPECIFICATIONS:

ALTERNATOR:

AXLES, SPRINGS & SHOCK ABSORBERS:

Front axle: Front springs: Rear axle: Rear springs:

Shocks absorbers:

**BACKUP ALARM:** BATTERIES:

**BODY ELECTRIC PANEL:** 

BRAKE SYSTEM:

Parking Brake:

**BUMPERS: CERTIFICATION:** 

**CHILD REMINDER:** 

CIRCUIT PROTECTION:

**COWL STEPS & GRIP HANDLES:** DOORS: Entrance:

Exit:

Vandal Locks:

Header Pad: (Entrance & Rear Exit Door):

**EMERGENCY EQUIPMENT:** 

240 amp, Leece Neville, 12 volt

12,000# rating, oil lubed bearings 10,000# capacity, "Softek" Parabolic tapered leaf 21,000# capacity, 5.29:1 ratio, oil lubed bearings

21,000# capacity, 2-Stage Direct acting, front and rear

112DB Safety alarm - operates while in reverse gear Three (3), 12 volt, Group 31, 2100 cca rating, enclosed with sliding tray & locking latch

> Exterior under driver window, with key lock Hydraulic System w/ Anti-lock (ABS)

Disc type front & rear, 70MM dual system (4) pistons per caliper Dust Shields, Brakes, front and rear

9" diameter x 3" wide, internal expanding, transmission mounted w/ interlock

Front-15" x 3/16", steel - Rear -12" x 3/16", steel Colorado Rack & Kentucky Pole Test Certified

**Altoona Tested** 

Doran, Sleeping Child Check System, Warning Light Activated

Manual resetting circuit breakers on body circuits Mounted LH & RH at windshield

**Double Outward type with Manual Door Control** 

Entrance door laminated glass, tinted 70% light transmittal 3-step step-well with black rubber ribbed step treads

Rear center mounted with upper/lower glass, tinted 30% light transmittal Retainer to hold door open

Black self-skinning foam

Entrance door equipped with key lock Rear door equipped with sliding bolt interlock

Per Oklahoma Requirements

5lb Fire Extinguisher, First Aid Kit, Warning Devices, Body Fluid Cleanup Kit & Seatbelt Cutter

**EMERGENCY EXITS:** 

Roof Hatches:

Push-out windows:

Two (2) combination escape hatch/vents Vertical Hinged, two (2) per side - four (4) per body **ENGINE: Cummins Diesel, Model B6.7L, 2017 EPA Emissions** 

> Horsepower rating: Torque rating:

220 hp @ 2400 rpm 600 lb-ft @ 1600 rpm

ENGINE COOLING SYSTEM: De-aeration system with tank & sight glass

Charge air & down-flow radiator mounted in tandem Cummins Compleat (Blue) Antifreeze (150,000 miles, / 4000hr. service)

ENGINE EQUIPMENT: Engine warning system, low oil pressure/high water temperature

Electric block heater, 750 watt, front bumper plug-in

Electromagnetic fan drive, Pre-set high idle switch, Cruise Control Firewall Insulation, Driver's Area

First two (2) ceiling panels (driver & 1st section): acoustic headlining

Diesel Particulate Filter (DPF), Selective Catalytic Reductant (SCR) & Diesel Exhaust Fluid (DEF) **EXHAUST SYSTEM (Primary):** 

Diesel Exhaust Fluid (DEF) Tank w/ a capacity of 15 gal., locking access door & marked "DEF"

Aluminized Tailpipe exits through rear bumper

Heavy Duty Black Rubber with aluminum aisle trim

5/8" plywood subflooring over steel floor, affixed with screws

100 gallon capacity, mounted between frame rails

90GPH, 10 Micron filter, heated Water in fuel sensor & primer pump

Floor mounted inspection plate, locking fuel tank access door

Speedometer, trip-odometer, tachometer, seven-digit odometer, clock, voltmeter

Oil pressure, coolant temperature, transmission temperature, fuel gauge

Glove box - below windshield, right side w/ latch & Console mounted armrest

Extra height headroom, 77 inches (6'5") at center aisle

90,000/btu

50,000/btu 80,000/btu

12 volt, on/off switch

Mounted upper center & upper left, 2-speed switch

Fiberglass tilting hood & fenders

Dual electric horns

Fiberglass/mineral wool, full body insulated Name of school district on beltline

**GVWR**, Capacity & Height - Exterior

Two (2) clear lens, 4" -rear, LED

Two (2) amber lens, grommet mount -front / Two (2) red lens, grommet mount -rear, LED Clearance lights:

Three (3) amber lens, grommet mount -front / Three (3) red lens, grommet mount -rear, LED

Two (2) amber lens -front, fender mounted / Two (2) amber lens, 7" -rear, LED

One (1) amber lens, per side, LED

Two rows, mounted above passenger seats, 15-candle power Single dome light for driver's area, separate switch

Doran 16-light monitor mounted in driver area

Exterior Light Test w/ Switch

Interior, operates with door control, incandescent

Two (2) red lens, 4" & Two (2) red lens, 7" -rear, LED

Roof Mounted, 18" from Rear, Clear, LED wired to switch

Eight (8) light system, non-sequential, LED with hoods ROSCO, Open View (ES) Split Mirror System, 7"x10" Flat Mirror & 7"x 10" Convex Mirror

Rearview exterior mirrors have black powder coated steel brackets

ROSCO, Eye-Max-LP Asymmetric Shaped Mirrors

Bell-Mount brackets for Cross-view Mirrors

All exterior mirrors are electrically heated, Rearview (exterior) are heated & remote controlled

6"x30" flat mirror, padded edge Black rubber mud flaps, front and rear

Black rubber fenders at rear wheel-housing opening

National School Bus Yellow with black trim

White

Two (2) year discoloration & Five (5) year

Exterior: Side, 20-gauge Fluted, 19/3/4" Skirts

Roof sheets, constructed of 20-gauge galvanized steel (window header to window

Ceiling Panels: 22-gauge steel, double-hemmed w/ rivet installation (No screws)

12 volt, mounted in switch panel, for cell phone, etc.

AM-FM-MP3-USB-PA Radio with eight (8) interior speakers 3M™ reflective vinyl, yellow

"SCHOOL BUS" in 8" black letters on 3M™ vellow reflective background. Front and Rear

Side & rear marker strips - marker strip surrounds each emergency exit

Four (4) double-ribbed, 16-gauge steel exterior body rub rails, painted black

DOT approved High Back School Bus Bench Seats

Grey Fire Block Upholstery

**ENGINE NOISE REDUCTION:** 

FLOOR COVERING:

**FUEL TANK:** 

Primary fuel filter / water separator:

GAUGES:

GLOVE BOX / CONSOLE: HEADROOM:

**HEATERS:** 

Left front heater & defroster: Right front heater & defroster: Rear under seat heater: Heater water booster pump:

Dual defroster fans:

**HOOD & FENDERS:** HORNS:

INSULATION: LETTERING:

LIGHTS: Backup lights:

> Identification lights: Directional lights: Directional lights, side:

Dome lights:

Monitor: Pre-Trip: Step-well light: Stop & Tail lights: Strobe Light: Warning lights:

MIRRORS: Exterior rearview:

Exterior cross-view:

Interior rearview:

MUD FLAPS & FENDERS:

PAINT: Exterior: Exterior roof: Warranty (Paint):

Interior

adhesion

PANELS:

header)

POWER SOCKET: RADIO: REFLECTIVE TAPE:

**RUB RAILS:** 

SEATS:

Passenger: Upholstery:

STEERING: STOPARM: SUNVISOR: SWITCHES:	Driver:	National Hi-back seat w/ mechanica Charcoal Cloth Upholstery, <b>Orange shoulder har</b> <b>Hydraulic power, tilt &amp; telescoping wh</b> 18" octagon sign w/flashing 6.5"X30", Green p Rocker type switches w/ latching r	rness & lap belt restraint eel, 50 degree wheel cut red lights, electric, LED blexi-glass, padded edge	
TIRES & RIMS:  TOW HOOKS: TRANSMISSION:	Front: Rear: Rims:		<b>lial</b> , LRH, Traction tread Hub Piloted, Disc Rims chassis frame mounted	
UNDERCOATING: WINDOWS:	Side, split sash: Rear, fixed panel: Entrance Door-& Driver Window:	5 speeds forward with overdrive - TranSynd® syn External transmission oil filter Underneat Tinted to allo Tinted to allo Tinted to allo	forward with overdrive - TranSynd® synthetic transmission fluid External transmission oil filter, Transmission oil cooler Underneath body fully undercoated Tinted to allow 30% light transmittal Tinted to allow 30% light transmittal Tinted to allow 70% light transmittal Two (2) piece curved, shaded	
safety plate WINDSHIELD WIP WIRING:	ERS: Chassis: Body:		nittent speed, w/washers LED readout on module	
windows WHEELBASE/TUR <b>WARRANTY</b> :	NING RADIUS: Body & Chassis: Body Three Year Extended Warranty: Chassis Powertrain / Fuel System:	273" wheelbase/3 Please Include Warranty Documentation Please Include Warranty Documentation PleaseIncludeWarrantyDocumentation	6'6" turning radius (wall)	
TOTAL UNIT CO		\$	-	
DELIVERY TIME:				
Optional Equipment: (NOT Included in above Pricing):				
1. VIDEO SURVEILLANCE SYSTEM: Gatekeeper Digital 304SD w/ two (2) lens additional, per bus  Note: One (1) software reader kit included				
ADD (1) additional	camera lens to system:	ad	ditional, per system, per	
<u>bus</u> ADD (2) additional <u>bus</u>	camera lens to system	ad	ditional, per system, per	
∞∞∞∞∞∞∞∞∞∞∞∞∞∞∞∞∞∞∞∞∞∞∞∞∞∞∞∞∞∞∞∞∞∞∞∞∞	xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx			
Dealership Repr	resentative	BID ACCEPTED BY SCHOO	DL DISTRICT OFFICIAL	
Date of Bid			ate of Acceptance	